



<b>TEST REPORT</b> <b>EN ISO 11148-4: 2012</b> <b>Hand-held non-electric power tools - Safety requirements</b> <b>- Part 4: Non-rotary percussive power tools</b>	
Report reference No. ....	SH11080399-010
Tested by (+ signature).....	Jonathan Chu 
Approved by (+ signature) .....	Michael Shen 
Date of issue .....	16 August, 2011
	Amendment-1: 12 April, 2013
	Amendment-2: 13 June, 2013
	<b>Amendment-3: 15 April, 2015</b>
Testing laboratory .....	Intertek Testing Services Shanghai Ltd.
Address.....	Building No.86, 1198 Qinzhou Road (North), Shanghai 200233, China
Testing location/procedure .....	TL <input checked="" type="checkbox"/> RMT <input type="checkbox"/> SMT <input type="checkbox"/> WMT <input type="checkbox"/> TMP <input type="checkbox"/>
Address.....	As above
Applicant.....	Ningbo Steed Tools Co., Ltd.
Address.....	Dongcheng Village, Zhanqi Town, Yinzhou District, Ningbo,Zhejiang,China
<b>Test specification:</b>	
Standard .....	EN ISO 11148-4: 2012
Test procedure .....	CE-MD
Non-standard test method .....	N/A
Test Report Form No .....	TTRF EN ISO 11148_4A
TRF Originator .....	Intertek Shanghai
Master TRF .....	2011-08
<b>Test Item Description</b> .....	
Trademark.....	N/A
Model and/or type reference.....	AT-2020, AT-2010, NST-2070F, NST-2080F, <b>NST-2080M, AT-2080, AT-2070</b>
Manufacturer.....	Same as applicant
Rating(s) .....	Max. air pressure: 6,3 bar
Remarks.....	None

**Test case verdicts**

Test case does not apply to the test object.....: N/A

Test item does meet the requirement .....: P(Pass)

Test item does not meet the requirement .....: F(Fail)

**Testing**

Date of receipt of test item .....: April 5,2015

Date(s) of performance of test .....: April 5,2015 --- April 15,2015

**General remarks**

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

"(See Enclosure #)" refers to additional information appended to the report.

"(See appended table)" refers to a table appended to the report.

Throughout this report a comma is used as the decimal separator.

Determination of the test results includes consideration of measurement uncertainty from the test equipment and methods.

**General product information:**

The products covered by this report are hand-held air hammer.

**Amendment 3:**

**This report based on report ref. no. SH11080399-010 issued on 16 August, 2011 with Amendment-1: 12 April, 2013 and Amendment-2: 13 June, 2013 by Intertek Testing Services Shanghai Limited including following changes and/or additions:**

**Add new models NST-2080M, AT-2070 in the report.**

## Copy of marking plate (Representative)



## Summary of testing:

All tests are carried out in accordance with the EN ISO 11148-4:2012 and the test results meet the requirements specified in the above-mentioned standards.

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
<b>4</b>	<b>Safety requirements and/or protective measures</b>		
<b>4.1</b>	<b>General</b>		
	The machine shall comply with the following safety requirements and/or protective measures and be verified in accordance with Clause 5. In addition, the machine shall be designed in accordance with the principles of ISO 12100 for the relevant, but not necessarily significant, hazards, which are dealt with by this part of ISO 11148.		P
<b>4.2</b>	<b>Mechanical safety</b>		
<b>4.2.1</b>	<b>Surfaces, edges and corners</b>		
	Accessible parts of non-rotary percussive power tools, except the inserted tool, shall not have sharp edges or angles or rough or abrasive surfaces; see ISO 12100:2010, 6.2.2.1.		P
<b>4.2.2</b>	<b>Supporting surface and stability</b>		
	The non-rotary percussive power tool shall be so designed that they can be laid aside and remain in a stable position on a plane surface.		P
<b>4.2.3</b>	<b>Ejection of parts</b>		
	Integral with or installed on a non-rotary percussive power tool shall be a retainer, without which the inserted tool has the possibility of being ejected when it is operated off a work surface.		P
<b>4.2.4</b>	<b>Hydraulic fluid ejection</b>		
	Hydraulic systems of the non-rotary percussive power tool shall be enclosed so as to give protection against high pressure fluid ejection.	Pneumatic	N/A
<b>4.2.5</b>	<b>Guards:</b>		
	Guards covering the inserted tool are not required.		P
<b>4.2.6</b>	<b>Power tool construction</b>		P
	The non-rotary percussive power tool shall be so designed and constructed as to prevent the loosening or loss of components during expected use, including rough handling and occasional dropping, which can compromise its safety functions.		P
<b>4.3</b>	<b>Thermal safety</b>		
	Surface temperatures of parts of the non-rotary percussive power tools that are held during use or that can be inadvertently touched shall follow the provisions of ISO 13732-1 and ISO 13732-3. Pneumatic tools shall be designed to avoid the cooling effects of exhaust air on the handles and other gripping zones.		P
<b>4.4</b>	<b>Noise</b>	See Clause 5.2	P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
<b>4.5</b>	<b>Vibration</b>	See Clause 5.3	P
<b>4.6</b>	<b>Materials and substances processed, used or exhausted</b>		
<b>4.6.1</b>	<b>Exhaust air or gas</b>		
	Non-rotary percussive power tools with compressed air or gas or an internal combustion engine shall be designed in such a way that exhaust air or gases are directed so as not to cause a hazard to the operator and so that any other effects, such as blowing the dust and reflected air or gas from the workpiece onto the operator, are minimized.		P
<b>4.6.2</b>	<b>Dust and fumes</b>		
	So far as is reasonably practicable, the non-rotary percussive power tool shall be designed to facilitate the collection and removal or suppression of airborne dust particles and fumes generated by the work process. The user instructions shall include sufficient information to enable adequate control of the risks from dust and fumes.		P
<b>4.6.3</b>	<b>Lubricants</b>		
	When specifying lubricants, the manufacturer shall take environmental and occupational health aspects into account.		P
<b>4.7</b>	<b>Ergonomics and design of the handle</b>		
	Gripping areas of the non-rotary percussive power tools shall be designed to provide a convenient, effective means for the operator to exercise full control over the non-rotary percussive power tool.		P
	Handles and other parts used for gripping the non-rotary percussive power tool shall be designed to ensure that the operator is able to grip the non-rotary percussive power tool correctly and to perform the expected work. Handles shall suit the functional anatomy of the hand and the dimensions of the hands of the operator population. Further guidance on ergonomic design principles can be found in EN 614-1		P
	Non-rotary percussive power tools having a mass greater than 2 kg (including the inserted tool) shall be capable of being supported by two hands whilst being lifted or operated.	≤ 2 Kg	N/A
	The grip shall be such that normal feed force can be transmitted in an ergonomic way from the hand of the operator to the non-rotary percussive power tool.		P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
<b>4.8</b>	<b>Controls</b>		
<b>4.8.1</b>	<b>Start-and-stop device</b>		
	Non-rotary percussive power tools shall be equipped with a single control device to start or stop them. It shall be adapted to the handle or to the part of the non-rotary percussive power tool being gripped, so that it can be held comfortably in the run position, and so that the operator can activate it without releasing the grip on the handles.		P
	Start-and-stop devices shall be so designed that the inserted tool ceases to be powered when the start-and stop device is released. Without manual effort and when completely released, the device shall move to the stop position, i.e. shall be of the hold-to-run type.	Hold to run type	P
	Start-and-stop devices shall be in the stop position or immediately move to the stop position when the assembly non-rotary percussive power tool for threaded fasteners is connected to the energy supply.	In the stop position	P
	It shall not be possible to lock the start-and-stop device in the running position.	No lock in the running position	P
	There are two exceptions.		N/A
	a) A small engraving tool may be equipped with a positive on-off throttle.		N/A
	b) A scaler whose chisel is integral with or fixed to the piston such that the piston-chisel cannot be expelled may be equipped with a positive on-off throttle.		N/A
<b>4.8.2</b>	<b>Unintentional start</b>		
	The start-and-stop device shall be designed, positioned or guarded that the risk of unintentional start is minimized. Verification shall be made according to 5.4		P
<b>4.8.3</b>	<b>Actuating forces</b>		
	For non-rotary percussive power tool that are intended for frequent starts or for use with precision work, the actuating force shall be small.		P
	For non-rotary percussive power tool that are normally used in operations of long duration, the force to keep the start device in the run position should be small.		P
	For further information on trigger forces for control devices see EN 894-3.		P
<b>5</b>	<b>Verification</b>		
<b>5.1</b>	<b>General conditions for tests</b>		
	Tests according to this part of ISO 11148 are type tests		P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
<b>5.2</b>	<b>Noise</b>		
	The noise-emission values shall be measured and reported in accordance with ISO 15744. The noise emission values and their uncertainties shall be declared in accordance with ISO 4871.	<b>Max of all models:</b> <b>L<sub>pA</sub>: 98 dB(A) K<sub>pA</sub>: 3 dB(A)</b> <b>L<sub>wA</sub>: 111 dB(A) K<sub>wA</sub>: 3 dB(A)</b>	P
	Compliance with 4.4 may be verified through the comparison of the noise emission values with those for other machines of the same family or with machines of similar size and performance characteristics.		P
<b>5.3</b>	<b>Vibration</b>		
	The vibration total value for non-rotary percussive power tools shall be measured and reported in accordance with ISO 28927-6 for rammers, ISO 28927-9 for hammers and breakers or ISO28927-10 for scaling hammers and needle scalers..	<b>Max of all models:</b> <b>10,6 m/s<sup>2</sup></b> <b>K= 1,5 m/s<sup>2</sup></b>	P
	The vibration-emission value and its uncertainty shall be declared in accordance with EN 12096.		P
	Compliance with 4.5 may be verified through the comparison of the vibration emission values with those for other machines of the same family or with machines of similar size and performance characteristics.		P
<b>5.4</b>	<b>Unintentional start</b>		
	Compliance with 4.8.2 shall be verified for non-rotary percussive power tools up to 15kg as follows.		P
	The retainer shall be mounted and not removed.		P
	The non-rotary percussive power tool shall be connected to the energy supply and placed and maintained in any possible position and pulled over the horizontal plane by its hose.		P
	Operation of the start-and-stop device shall not occur.		P
<b>5.5</b>	<b>Power tool construction</b>		
	Except for breakers, compliance with 4.2.6 shall be verified by dropping a sample non-rotary percussive power tool three times onto a concrete surface from a height of 1 m without affecting its operational and safety functions. The sample shall be positioned to vary the point of impact.		P
<b>5.6</b>	<b>Structure of verification of safety requirements</b>		
	Table 1 — Structure of verification	Satisfy the table 1	P
<b>6</b>	<b>Information for use</b>		
<b>6.1</b>	<b>Marking, signs and written warnings</b>		
	Non-rotary percussive power tool shall be marked visibly, legibly and indelibly with the following information		

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	name and full address of the manufacturer and, where applicable, his/her authorized representative		P
	designation of series or type		P
	serial number or batch number;		P
	year of construction, that is the year in which the manufacturing process is completed;		P
	for pneumatic non-rotary percussive power tools: the rated air pressure marked as (max.)		P
	for hydraulic non-rotary percussive power tools: the nominal pressure and flow the maximum allowable setting for the pressure relief valve		N/A
	Non-rotary percussive power tools shall be permanently marked with a graphical symbol in accordance with Annex C showing that the operator's instructions shall be read before work starts.		P
<b>6.2</b>	<b>Instruction handbook</b>		
<b>6.2.1</b>	<b>General</b>		
	For the information provided to the user, the content of Clause 6 together with ISO 12100:2010, 6.4.5.2 and 6.4.5.3, apply.	See copy of manual	P
	The information provided by the manufacturer is an important but not exclusive basis for the safe use of the non-rotary percussive power tool. It shall provide sufficient information for the end user to perform an initial risk assessment.		P
	The hazards identified in 6.2.2.4 to 6.2.2.11 are foreseeable in the general use of non-rotary percussive power tools. The information provided with the non-rotary percussive power tool shall state that the user or the user's employer shall assess the specific risks that can be present as a result of each use.		P
	The instruction handbook shall contain information relating to at least the following:		P
	name and address of the manufacturer or supplier or any other agent responsible for placing the Non-rotary percussive power tool on the market;		P
	designation of the series or type;		P
	operating instructions; see 6.3;		P
	information on noise emission; see 6.4.2;		P
	information on vibration transmitted to the hands of the operator; see 6.4.3		P
	maintenance instructions; see 6.5		P
	explanations of any symbols marked on the non-rotary percussive power tool; see Annex C;		P
	information about residual risks and how to control them		P



EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
<b>6.2.2</b>	<b>Operator's instructions</b>		
<b>6.2.2.1</b>	<b>Statement of use</b>		
	The operator's instructions shall include a description of the correct use of the non-rotary percussive power tool and make reference to the appropriate inserted tools. The operator's instructions shall state that any other use is forbidden. Foreseeable misuse of the non-rotary percussive power tool, which experience has shown to occur, shall be warned against.		P
<b>6.2.2.2</b>	<b>Allowance for user</b>		
	The operator's instructions shall be written primarily for professional users. Where a tool can be used by nonprofessional users, additional information for use shall be provided		P
<b>6.2.2.3</b>	<b>General safety rules</b>		
	Warnings shall be given with regard to significant hazards arising from or associated with the use of the non-rotary percussive power tool.		P
	The following is a non-exhaustive list. Manufacturers may add additional warnings.		P
	For multiple hazards, read and understand the safety instructions before installing, operating, repairing, maintaining, changing accessories on, or working near the non-rotary percussive power tool. Failure to do so can result in serious bodily injury.		P
	Only qualified and trained operators should install, adjust or use the non-rotary percussive power tool.		P
	Do not modify this non-rotary percussive power tool. Modifications can reduce the effectiveness of safety measures and increase the risks to the operator.		P
	Do not discard the safety instructions; give them to the operator.		P
	Do not use the non-rotary percussive power tool if it has been damaged.		P
	Tools shall be inspected periodically to verify that the ratings and markings required by this part of ISO 11148 are legibly marked on the tool. The employer/user shall contact the manufacturer to obtain replacement marking labels when necessary.		P
<b>6.2.2.4</b>	<b>Projectile hazards</b>		
	The following apply		P
	Disconnect the non-rotary percussive power tool from the energy source when changing inserted tool or accessories.		P
	Be aware that failure of the workpiece, or accessories, or even of the inserted tool itself can generate high-velocity projectiles.		P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	Always wear impact-resistant eye protection during the operation of the non-rotary percussive power tool. The grade of protection required should be assessed for each use.		P
	For overhead work, wear a safety helmet.		P
	The risks to others should also be assessed at this time.		P
	Ensure that the workpiece is securely fixed.		P
	Never operate a tool unless the inserted tool is retained in the tool with a proper retainer.		P
	To avoid injury, retainer parts shall be replaced when they become worn, cracked or distorted.		P
	Hold the inserted tool firmly against the work surface before starting the tool.		P
<b>6.2.2.5</b>	<b>Operating hazards</b>		
	The following apply		P
	The use of the tool can expose the operator's hands to hazards including impacts, cuts and abrasions and heat. Wear suitable gloves to protect hands.		P
	Operators and maintenance personnel shall be physically able to handle the bulk, weight and power of the tool.		P
	Hold the tool correctly; be ready to counteract normal or sudden movements and have both hands available.		P
	Maintain a balanced body position and secure footing		P
	Release the start-and-stop device in the case of an interruption of the energy supply.		P
	Use only lubricants recommended by the manufacturer		P
	Avoid direct contact with the inserted tool during and after use as it can become hot.		P
	Personal protective safety glasses shall be used; suitable gloves and protective clothing are recommended.		P
<b>6.2.2.6</b>	<b>Repetitive motions hazards</b>		
	The following apply		P
	When using a non-rotary power tool to perform work-related activities, the operator can experience discomfort in the hands, arms, shoulders, neck, or other parts of the body.		P
	While using an non-rotary percussive power tool, the operator should adopt a comfortable posture whilst maintaining a secure footing and avoiding awkward off-balanced postures. The operator should change posture during extended tasks, which can help avoid discomfort and fatigue		P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	If the operator experiences symptoms such as persistent or recurring discomfort, pain, throbbing, aching, tingling, numbness, burning sensations or stiffness, these warning signs should not be ignored. The operator should tell the employer and consult a qualified health professional.		P
<b>6.2.2.7</b>	<b>Accessory hazards</b>		
	The following apply.		P
	Disconnect the non-rotary percussive power tool from the energy supply before changing the inserted tool or accessory.		P
	Only use sizes and types of accessories and consumables that are recommended by the non-rotary percussive power tool manufacturer		P
	For hammers, where appropriate, never use any chisel as a hand-struck tool. They are specifically designed and heat-treated for use only in non-rotary percussive power tools.		P
	For hammers and breakers, where appropriate, never use blunt chisels, as they require excessive pressure and can break from fatigue. Blunt tool-pieces can increase vibration and, therefore, sharp tools should always be used.		P
	For hammers, where appropriate, never cool a hot accessory in water. Brittleness and early failure can result.		P
	For hammers, where appropriate, chisel breakage or tool damage can result from misuse of using the tool as a lever, e.g. prising. Take smaller "Bites" to avoid getting stuck.		P
	Avoid direct contact with the inserted tool during and after use, as it can be hot or sharp.		P
<b>6.2.2.8</b>	<b>Workplace hazards</b>		
	The following apply		P
	Slips, trips and falls are major causes of workplace injury. Be aware of slippery surfaces caused by the use of the tool and also of trip hazards caused by the air line or hydraulic hose		P
	Proceed with care in unfamiliar surroundings. Hidden hazards, such as electricity or other utility lines, can exist		P
	The non-rotary percussive power tool is not intended for use in potentially explosive atmospheres and is not insulated against coming into contact with electric power		P
	Make sure there are no electrical cables, gas pipes, etc., that can cause a hazard if damaged by use of the tool		P
<b>6.2.2.9</b>	<b>Dust and fume hazards</b>		
	The following apply		P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	Dust and fumes generated when using non-rotary percussive power tools can cause ill health (for example, cancer, birth defects, asthma and/or dermatitis); risk assessment and implementation of appropriate controls for these hazards are essential.		P
	Risk assessment should include dust created by the use of the tool and the potential for disturbing existing dust.		P
	Operate and maintain the non-rotary percussive power tool as recommended in the instruction handbook, to minimize dust or fume emissions.		P
	Direct the exhaust so as to minimize disturbance of dust in a dust-filled environment		P
	Where dust or fumes are created, the priority shall be to control them at the point of emission		P
	All integral features or accessories for the collection, extraction or suppression of airborne dust or fumes should be correctly used and maintained in accordance with the manufacturer's instructions.		P
	Select, maintain and replace the consumable/inserted tool as recommended in the instructions, to prevent an unnecessary increase in dust or fumes.		P
	Use respiratory protection in accordance with employer's instructions and as required by occupational health and safety regulations.		P
<b>6.2.2.10</b>	<b>Noise hazards</b>		
	The following apply.		P
	Unprotected exposure to high noise levels can cause permanent, disabling hearing loss and other problems, such as tinnitus (ringing, buzzing, whistling or humming in the ears).		P
	Risk assessment and implementation of appropriate controls for these hazards are essential		P
	Appropriate controls to reduce the risk may include actions, such as damping materials to prevent workpieces from "ringing".		P
	Use hearing protection in accordance with employer's instructions and as required by occupational health and safety regulations.		P
	Operate and maintain the non-rotary percussive power tool as recommended in the instruction handbook, to prevent an unnecessary increase in noise levels.		P
	If the rotary percussive power tool has a silencer, always ensure it is in place and in good working order when the non-rotary percussive power tool is operating.		N/A
<b>6.2.2.11</b>	<b>Vibration hazards</b>		

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	The information for use shall draw attention to vibration hazards that have not been eliminated by design and construction and remain as residual vibration risks. It shall enable employers to identify the circumstances in which the operator is likely to be at risk from vibration exposure. If the vibration emission value obtained using ISO 28927-6 for rammers, ISO 28927-9 for hammers and breakers and ISO 28927-10 for scaling hammers and needle scalers does not adequately represent the vibration emission in the intended uses (and foreseeable misuses) of the machine, additional information and/or warnings shall be supplied to enable the risks arising from vibration to be assessed and managed.		P
	The following warnings (or equivalent) shall be given.		P
	Exposure to vibration can cause disabling damage to the nerves and blood supply of the hands and arms		P
	Wear warm clothing when working in cold conditions and keep your hands warm and dry.		P
	If you experience numbness, tingling, pain or whitening of the skin in your fingers or hands, stop using the non-rotary percussive power tool, tell your employer and consult a physician.		P
	Operate and maintain the non-rotary percussive power tool as recommended in the instruction handbook, to prevent an unnecessary increase in vibration levels		P
	Do not hold the inserted tool with the free hand, as this increases vibration exposure.		P
	Hold the tool with a light but safe grip, taking account of the required hand reaction forces, because the risk from vibration is generally greater when the grip force is higher.		P
	Keep suspended handles in the central position and avoid pushing the handles into the end stops.		N/A
	For breakers, cut small "bites" of concrete to prevent the tool from jamming.		N/A
	For breakers, move the cutting tool every few seconds. Stop the breaker when lifting the tool to change position, because vibration is high when pulling up on the handles.		N/A
<b>6.2.3</b>	<b>Additional safety instructions for pneumatic power tools</b>		
	The following additional warnings (or equivalent) shall be given with all pneumatic non-rotary percussive power tools.		P
	Air under pressure can cause severe injury:		P
	always shut off air supply, drain hose of air pressure and disconnect tool from air supply when not in use, before changing accessories or when making repairs;		P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	never direct air at yourself or anyone else.		P
	Whipping hoses can cause severe injury. Always check for damaged or loose hoses and fittings		P
	Cold air shall be directed away from the hands		P
	Do not use quick-disconnect couplings at tool inlet. Use hardened steel (or material with comparable shock resistance) threaded hose fittings		P
	Whenever universal twist couplings (claw couplings) are used, lock pins shall be installed and whipcheck safety cables shall be used to safeguard against possible hose-to-tool and hose-and-hose connection failure.		P
	Do not exceed the maximum air pressure stated on the tool.		P
	Never carry an air tool by the hose.		P
<b>6.2.4</b>	<b>Additional safety instructions for hydraulic power tools</b>		
	The following additional warnings (or equivalent) shall be given with all hydraulic non-rotary percussive power tools.		N/A
	Do not exceed the maximum relief-valve setting stated on the tool		N/A
	Carry out a daily check for damaged or worn hoses or hydraulic connections and replace if necessary		N/A
	Use only clean oil and filling equipment		N/A
	Power units require a free flow of air for cooling purposes and should, therefore, be positioned in a well ventilated area free from hazardous fumes.		N/A
	Ensure that couplings are clean and correctly engaged before operation		N/A
	Do not inspect or clean the tool while the hydraulic power source is connected. Accidental engagement of the tool can cause serious injury		N/A
	Do not install or remove the tool while the hydraulic power source is connected. Accidental engagement of the tool can cause serious injury		N/A
	Be sure all hose connections are tight.		N/A
	Wipe all couplers clean before connecting. Failure to do so can result in damage to the quick couplers and cause overheating.		N/A
	Instructions shall be given that only hydraulic fluid recommended by the manufacturer shall be used.		N/A
<b>6.2.5</b>	<b>Specific safety instructions</b>		
	Warnings shall be given about any specific or unusual hazards associated with the use of the non-rotary percussive power tool. Such warnings shall indicate the nature of the hazard, the risk of injury and the avoidance action to take.		P
<b>6.3</b>	<b>Operating instructions</b>		
	The instructions shall include, where appropriate		P

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	instructions for setting up or fixing the non-rotary percussive power tool in a stable position as appropriate for non-rotary percussive power tool that can be mounted in a support		P
	assembly instructions, accessories and inserted tools		P
	illustrated description of functions;		P
	limitation on tool use due to environmental conditions		P
	instructions for setting and testing		P
	general instructions for use, including changing inserted tools and limits on the size and type of workpiece		P
<b>6.4</b>	<b>Data</b>		
<b>6.4.1</b>	<b>General</b>		
	The instructions shall include the information on the data plate and the following		P
	mass of the non-rotary percussive power tool		P
	for hydraulic non-rotary percussive power tool		N/A
	specification of the coupling		N/A
	specification of hoses with regard to pressure and flow		N/A
	maximum inlet temperature of the inlet fluid		N/A
<b>6.4.2</b>	<b>Noise</b>		
<b>6.4.2.1</b>	<b>Declaration of emission</b>		
	The instructions shall include the noise-emission values and uncertainties as specified in 5.2 and the reference number of the test code, ISO 15744.		P
<b>6.4.2.2</b>	<b>Additional information</b>		
	If the values for noise emissions obtained using the appropriate tests defined in 5.2 do not adequately represent the emissions during the intended uses of the machine, additional information and/or warnings shall be supplied to enable the potential risks to be assessed and managed.		N/A
	Information on noise emission should also be provided in the sales literature.		P
<b>6.4.3</b>	<b>Vibration</b>		
<b>6.4.3.1</b>	<b>Declaration of emission</b>		
	The instruction handbook shall include the vibration-emission value and uncertainty as specified in 5.3 and the reference number of the test code, ISO 28927-6, ISO 28927-9 or ISO 28927-10.		P
<b>6.4.3.2</b>	<b>Additional information</b>		

EN ISO 11148-4:2012			
Clause	Requirement - Test	Result - Remark	Verdict
	If the values for vibration emissions obtained using the appropriate tests defined in 5.3 do not adequately represent the emissions during the intended uses of the machine, additional information and/or warnings shall be supplied to enable the potential risks to be assessed and managed		N/A
	Information on vibration emission should also be provided in the sales literature.		P
<b>6.5</b>	<b>Maintenance instructions</b>		
	The maintenance instructions shall contain		P
	instructions to keep the non-rotary percussive power tool safe by regular preventative maintenance		P
	information on when the regular preventative maintenance shall be carried out, for instance, after a specified time of operation, a specified number of cycles/operations or a stated number of times per year		P
	instructions for disposal so as not to expose personnel and the environment to hazards		P
	list of the service operations that the user should carry out		P
	instructions for lubrication, if required		P
	instructions to check the speed and make a simple check of the vibration level after each service		P
	instructions to check the speed regularly		P
	specifications of the spare parts for use when these affect the health and safety of operators		P
	Maintenance instructions shall include the precautions to take to avoid exposure to hazardous substances deposited (due to work processes) on the tool		P
<b>Annex A</b>	<b>List of significant hazards</b>		
<b>Annex B</b>	<b>Examples of non-rotary percussive power tools covered by this part of ISO 11148</b>		
<b>Annex C</b>	<b>Symbols for labels and signs</b>		
<b>Annex D</b>	<b>Additional safety requirements related to internal combustion engine power tools</b>		N/A